

OdaLog[®]

METHANOMETER



Mining and Industrial Models

360° Visual Alarm

Audible Alarm

Rechargeable Batteries

Over 12 Hour Continuous Operation

Large Illuminated Display

30000 point Data Logging and Download

User Selectable Alarm Level

Lightweight and Robust Design

Corrosion Resistant

It's Blinking Good !



App-Tek
INTERNATIONAL PTY LTD

**F
L
A
M
M
A
B
L
E

G
A
S

M
O
N
I
T
O
R
S**

OdaLog[®]

SPECIFICATIONS

**F
L
A
M
M
A
B
L
E
G
A
S
M
O
N
I
T
O
R
S**

| Sensor Type | CH ₄ | Flammable Gas |
|--|--|-----------------|
| Range | 0- 5% VOL | 0-100% LEL |
| Resolution | 0.01% VOL | 1% LEL |
| Calibrated Accuracy at 2.5% VOL at STP | ± 0.1 % VOL | ± 2 % LEL |
| Max Zero Drift in clean air at STP | ± 0.25 % /Month | ± 5 % LEL/Month |
| Max Zero Shift (20° – 40° C) | ±0.1 % VOL | ± 2% LEL |
| Repeatability at 2.5% VOL at STP | ± 0.1% VOL | ± 2% LEL |
| Response Time | T50 < 20 seconds T90 < 60 seconds | |
| Pressure Range | Atmospheric ± 10 % | |
| Relative Humidity Range | 0-95 % (Non-condensing) | |
| LCD Display | 0000 - 9999 | |
| Instrument Temp Range | 0° C to 40° C 32 ° F to 104 ° F | |
| External Dimensions | 165mm x 62mm Diameter 6.5" x 2.44" Diameter | |
| Instrument Weight | 580 Grams 1lb 3oz | |
| Battery Life | 12 Hours Plus | |
| Data Logging Capacity | 30000 Readings | |
| Interval | Selectable from 10 second to 1 hour | |
| Intrinsic Safety | Ex ia, s, I/IIC T4, IP66 AUS Ex 02.1545 | |

Authorised Distributor

13/6 Pinnacle Street
(PO Box 5523)
Brendale QLD 4500
Australia

App-Tek
INTERNATIONAL PTY LTD

ABN 28 089 678 339
www.App-Tek.com

In the interest of continued improvement, we reserve the right to change design features without prior notice.